

Falcon[®] HR

Traffic Safety RADAR



The reliable choice for hand-held Directional K-Band Radar.

High Performance

- Directional Doppler radar system
- Digital Signal Processing (DSP) for tracking multiple targets
- TruTrak[®]'s VSS interface, with dash mount option, allows automatic mode switching between moving and stationary modes eliminating patrol shadowing and combining errors
- Track thru lock supports tracking history after target lock
- Smart Patrol Search rejects inaccurate patrol speeds
- Displays fastest target quicker than leading competitor

Low Power

- FCC Type 15 device
- Long battery life and low transmitted power

Easy to Read

- LCD non-multiplexed display for improved readability
- LED backlight for night time operation
- Simple push button user interface
- Auto self-test with every locked target

Operational Configurations

- Upgradeable to moving operation with IR or wired remote
- Moving same lane option
- Handle on or pod mount for moving operation
- Interchangeable accessories with the Talon family including battery handle, pod mount, etc.
- Narrow 12° beam width for improved targeting
- IACP conforming products list



Easily readable in direct sunlight

High performance K-band

Moving operation available

Directional K-band

Falcon[®] HR

Traffic Safety RADAR



Standard Package includes

- Corded handle
- Stationary operation
- Direction sensing/selection
- Fastest vehicle mode

Optional Accessories

- Battery handle
- Quick charger in car
- Pod module
- Pod module with wired remote, ICV cables
- Carrying case
- Data Logger
- Printer

Specifications

Frequency: K-band 24.125 GHz (+/- 100 MHz)
Beam Width: 12° horizontal
Operating Voltage: Corded: 10 to 16.5V DC, Cordless: 7.2V DC
Weight: 2.0 lbs. (0.9 kg) with battery handle
Speed Accuracy: Stationary +/- 1 mph (+/- 1 kph)
Moving: +1/- 2 mph (+2/-3 kph)
Standard Warranty: 2 Years

Typical Performance

Stationary

5 to 200 mph (8 to 321 kph)

Moving

5 to 120 mph (8 to 193 kph)

Target Opposite Direction

20 to 200 mph (32 to 321 kph)

Same Direction

3 mph to 65% of Patrol (5 kph to 65% of Patrol)



Stationary, approaching, receding or all directions



Directional K-band



Handle on and pod mount

Falcon HR - Data Sheet - USA Eng - Print - 06/2013